

## FIRE EXTINGUISHING TUBES HALOCARBON GAS FIRE EXTINGUISHERS



- CE 0036 Certified.
- TS 862 EN 3 Certified.
- ISO 9001 Certified.
- 2-year warranty..
- N2 (Nitrogen) propellant.
- Body is made of longdrawn steel, welded seamless, monolithic.
- -20°C / +60°C operating temperature.
- Safety valve
- With hanger
- Fire extinguishing medium: Halocarbon gas

CAPACITY	TYPE	EXTINGUISHER CLASS	OPERATING PRESSURE	TEST PRESSURE	SPRAY DISTANCE
1 kg	Portable Type	A,B	17 Bar	25 Bar	3 - 4 m.
2 kg	Portable Type	A,B	17 Bar	25 Bar	3 - 4 m.
4 kg	Portable Type	A,B	17 Bar	25 Bar	3 - 4 m.
6 kg	Portable Type	A,B	17 Bar	25 Bar	3 - 4 m.
12 kg	Portable Type	A,B	17 Bar	25 Bar	3 - 4 m.

- Preferred in fires which caused by computing rooms, UPS, computer environments, high voltage panels, transformers, electronic circuits and devices.

## WATER FIRE EXTINGUISHING TUBES



- CE 0036 Certified.
- TS 862 EN 3 Certified.
- ISO 9001 Certified.
- 2 year warranty.
- N2 (Nitrogen) propellant.
- Body is made of longdrawn steel, welded seamless, monolithic.
- -20°C / +60°C operating temperature.
- Safety valve
- With hanger
- Extinguishing agent: Water

CAPACITY	TYPE	EXTINGUISHER CLASS	OPERATING PRESSURE	TEST PRESSURE	SPRAY DISTANCE
6 kg	Portable Type	A	17 Bar	25 Bar	3 - 4 m.

- Preferred in fires caused by materials of organic origin such as paper, cotton, straw, wood, coal, textile, products.