

## FOAM SYSTEM FIRE CABINET | 1" SEMI – RIGID HOSE REEL, AXIAL WATER SUPPLY



- All parts are painted with electrostatic powder paint at 200°C, optionally in the colours RAL 9010 white, RAL 3003 red or RAL 1013 champagne.
- Fire cabinets and their doors can be optionally produced from stainless steel and with decorative cutouts to suit various architectural requirements.

CODE	MOUNTING STYLE	MODULAR DOOR TYPE	HOSE DIAMETER & CAPACITY	TANK CAPACITY	LIGHTING	W mm	H mm	H <sub>1</sub> mm	H <sub>2</sub> mm	D mm
K4-112.1	Recessive – Surface	Full Overlay Steel, Chrome Plated Handle	1" - 20 m	50 l	Optional	800	1550	1400	150	300
K4-112.2	Recessive – Surface	Full Overlay Steel, Chrome Plated Handle	1" - 25 m	50 l	Optional	800	1550	1400	150	300
K4-112.3	Recessive – Surface	Full Overlay Steel, Chrome Plated Handle	1" - 30 m	50 l	Optional	800	1550	1400	150	300
K4-115.1	Recessive – Surface	Full Overlay Glass	1" - 20 m	50 l	Optional	800	1550	1400	150	300
K4-115.2	Recessive – Surface	Full Overlay Glass	1" - 25 m	50 l	Optional	800	1550	1400	150	300
K4-115.3	Recessive – Surface	Full Overlay Glass	1" - 30 m	50 l	Optional	800	1550	1400	150	300

### ► CABINET HOUSING

- Produced from 1.5 mm mild steel (DKP).
- Foam tank made of stainless steel. with 50l capacity. The tank capacity can be increased depending on demand.
- Recessive or surface mount type obtainable

### ► HOSE REEL

- Axial water supply. Water inlet made of rust-resistant material.
- Solid 6 mm crank allows hose reel to be opened at an angle of 270°.
- Includes 2" fire valve and 2" x1" reducing valve.
- 1" foam nozzle
- 1" round, semi – rigid hose.
- Inside hardened connection hose connects hose reel with valve
- All connections are made with press fitting instead of clamp fitting
- All hose reels have been tested.
- 50 l %3 AFFF (Aqueous Film Forming) Foam Capacity can be increased on demand.
- 1" foam mixer

### ► CABINET DOOR

- Modular full overlay metal sheet doors with chrome plated handle or full overlay glass doors obtainable
- Warning signs on the surface
- After the housing has been mounted on the wall, the doors can be simply attached to the housing with 4 screws.
- 180 degree opening door with semi-hidden continuous hinges.