

FIRE CABINET

1" SEMI – RIGID HOSE REEL, AXIAL WATER SUPPLY

HOSE REEL WITH RAIL SYSTEM, FIRE EXTINGUISHER SECTION



▶ SE1-1922.1

▶ SE1-1925.1

- All parts are painted with electrostatic powder paint at 200°C, optionally in the colours RAL 9010 white, RAL 3003 red or RAL1013 champagne. Other colours are available to meet specific needs.
- This fire cabinet models are in compliance with EN 671-1.
- Fire cabinets and their doors can be optionally produced from stainless steel and with decorative cutouts to suit various architectural requirements.

CODE	MOUNTING STYLE	MODULAR DOOR TYPE	HOSE DIAMETER & LENGTH	TUBE CAPACITY	W mm	H mm	D mm
SE1-1922.1	Recessed and Surface	Full Overlay Metal Sheet Door, Chrome Plated Handle	1" - 20 m	1 Tube / 6 kg	350	1220	670
SE1-1922.2	Recessed and Surface	Full Overlay Metal Sheet Door, Chrome Plated Handle	1" - 25 m	1 Tube / 6 kg	350	1220	670
SE1-1922.3	Recessed and Surface	Full Overlay Metal Sheet Door, Chrome Plated Handle	1" - 30 m	1 Tube / 6 kg	350	1220	670
SE1-1925.1	Recessed and Surface	Full Overlay Glass Door	1" - 20 m	1 Tube / 6 kg	350	1220	670
SE1-1925.2	Recessed and Surface	Full Overlay Glass Door	1" - 25 m	1 Tube / 6 kg	350	1220	670
SE1-1925.3	Recessed and Surface	Full Overlay Glass Door	1" - 30 m	1 Tube / 6 kg	350	1220	670

▶ CABINET HOUSING

- Produced from 1.2 mm mild steel (DKP).
- Flaps at every corner for fire valve installation.
- Hose reel can be left or right mounted.
- Surface mount or recessed mount types obtainable.

▶ HOSE REEL

- Axial water supply. Water inlet made of rust-resistant material.
- Special rail system ensures the movement of the hose reel
- 1" slide valve
- Nozzle with 1" jet / spray / lock setting.
- 1" round, semi – rigid hose.
- Inside hardened connection hose connects hose reel with valve
- All connections are made with press fitting instead of clamp fitting
- All hose reels have been tested.

▶ CABINET DOOR

- Full overlay glass or metal sheet door, chrome plated handle
- Warning signs on the surface
- After the housing has been mounted on the wall, the doors can be simply attached to the housing with 4 screws.
- 180 degree opening door with semi-hidden continuous hinges.