

FIRE CABINET

1" SEMI - RIGID HOSE REEL, AXIAL WATER SUPPLY


INSET METAL SHEET DOOR, DOUBLE REEL, HORIZONTAL FIRE EXTINGUISHER SECTION



- All parts are painted with electrostatic powder paint at 200°C, optionally in the colours RAL 9010 white, RAL 3003 red or RAL1013 champagne. Other colours are available to meet specific needs.
- This fire cabinet models are in compliance with EN 671-1.
- Fire cabinets and their doors can be optionally produced from stainless steel and with decorative cutouts to suit various architectural requirements.
- All models can be manufactured with front and rear doors.







▶ SE1-2313.1

CODE	MOUNTING STYLE	MODULAR DOOR TYPE	HOSE DIAMETER & LENGTH	TUBE CAPACITY	LIGHTING	W mm	H mm	D mm	W, mm	H, mm
SE1-2313.1	Recessed	Inset Metal Sheet Door	1" - 20 m	1 Tube / 6 kg	Optional	700	1800	200	660	1760
SE1-2313.2	Recessed	Inset Metal Sheet Door	1" - 25 m	1 Tube / 6 kg	Optional	700	1800	200	660	1760
SE1-2313.3	Recessed	Inset Metal Sheet Door	1" - 30 m	1 Tube / 6 kg	Optional	700	1800	200	660	1760
SE1-2323.1	Surface	Inset Metal Sheet Door	1" - 20 m	1 Tube / 6 kg	Optional	700	1800	200	700	1800
SE1-2323.2	Surface	Inset Metal Sheet Door	1" - 25 m	1 Tube / 6 kg	Optional	700	1800	200	700	1800
SE1-2323.3	Surface	Inset Metal Sheet Door	1" - 30 m	1 Tube / 6 kg	Optional	700	1800	200	700	1800

CABINET HOUSING

- Produced from 1.2 mm mild steel (DKP).
- Flaps at every corner for fire valve installation
- Hose reel can be left or right mounted
- Surface mount or recessed mount types obtainable.

▶HOSE REEL

- Axial water supply. Water inlet made of rust-resistant material.
- Solid 6 mm crank allows hose reel to be opened at an angle of 270°.
- Includes 2" fire valve and 2" x1" reducing valve.
- Nozzle with 1" jet / spray / lock setting.
- 1" round, semi rigid hose.
- Inside hardened connection hose connects hose reel with valve
- All connections are made with press fitting instead of clamp fitting
- All hose reels have been tested.

CABINET DOOR

- Inset metal sheet door with radial frame, chrome plated handle
- Relief warning signs on the surface
- After the housing has been mounted on the wall, the doors can be simply attached to the housing with 4 screws.
- 180 degree opening door with continuous hinges, optionally stainless hinges or invisible hinges obtainable.