


FIRE CABINET


1" SEMI – RIGID HOSE REEL, AXIAL WATER SUPPLY

INSET METAL SHEET, DOUBLE DOOR, DOUBLE HOSE REEL, VERTICAL FIRE EXTINGUISHER SECTION FOR 2 TUBES



- All parts are painted with electrostatic powder paint at 200°C, optionally in the colours RAL 9010 white, RAL 3003 red or RAL1013 champagne. Other colours are available to meet specific needs.
- This fire cabinet models are in compliance with EN 671-1.
- Fire cabinets and their doors can be optionally produced from stainless steel and with decorative cutouts to suit various architectural requirements.
- · All models can be manufactured with front and rear doors.





W₁

810

810 1560

810 1560

850

850 1600

850 1600

H.

1560

1600

CODE MOUNTING STYLE MODULAR DOOR TYPE **HOSE DIAMETER &** TUBE CAPACITY LIGHTING W н D LENGTH SE1-2613.1 Inset Metal Sheet, Double Door 2 Tubes / 6 kg Recessed 1" - 20 m 850 1600 200 Optional SE1-2613.2 Inset Metal Sheet, Double Door 1" - 25 m 2 Tubes / 6 kg Recessed Optional 850 1600 200 SE1-2613.3 Recessed Inset Metal Sheet, Double Door 1" - 30 m 2 Tubes / 6 kg Optional 850 1600 200 SE1-2623.1 Surface Inset Metal Sheet, Double Door 1" - 20 m 2 Tubes / 6 kg Optional 850 1600 200 SE1-2623.2 Surface Inset Metal Sheet, Double Door 1" - 25 m 2 Tubes / 6 kg Optional 850 1600 200 SE1-2623.3 Inset Metal Sheet, Double Door 1" - 30 m 2 Tubes / 6 kg Surface Optional 850 1600 200

CABINET HOUSING

- Produced from 1.2 mm mild steel (DKP).
- Flaps at every corner for fire valve installation.
- Hose reel can be left or right mounted.
- Surface mount or recessed mount types obtainable.

HOSE REEL

- Axial water supply. Water inlet made of rust-resistant material.
- Solid 6 mm crank allows hose reel to be opened at an angle of 270°.
- Includes 2" fire valve and 2" x1" reducing valve.
 Nozzle with 1" jet / spray / lock setting.
- Nozzie with T jet / spray / lock set
 1" round, semi rigid hose.
- Inside hardened connection hose connects hose reel
- with valve
- All connections are made with press fitting instead of clamp fitting
- All hose reels have been tested.

CABINET DOOR

- Inset metal sheet door with radial frame, chrome plated handle
- Relief warning signs on the surface.
- After the housing has been mounted on the wall, the doors can be simply attached to the housing with 4 screws.
- 180 degree opening door with continuous hinges, optionally stainless hinges or invisible hinges obtainable.

We reserve the right to make changes in design and size. | Our products are patented by the Turkish Patent Office