

FIRE CABINET


LAY- FLAT HOSE

FULL OVERLAY METAL SHEET DOOR, CHROME PLATED HANDLE



SE2-2212.1

- 2½" flat type fire hose, 2½" fire valve and 2½" fire lance are optional
- All parts are painted with electrostatic powder paint at 200°C, optionally in the colours RAL 9010 white, RAL 3003 red or RAL1013 champagne. Other colours are available to meet specific needs.
- This fire cabinet models are in compliance with EN 671-1.
- Fire cabinets and their doors can be optionally produced from stainless steel and with decorative cutouts to suit various



| CODE | MOUNTING STYLE | MODULAR DOOR TYPE | HOSE DIAMETER & LENGTH | TUBE CAPACITY | LIGHTING | W mm | H mm | D mm | W ₁ mm | H ₁ mm |
|------------|----------------|---|------------------------|---------------|----------|---------|---------|---------|----------------------|----------------------|
| SE2-2212.1 | Recessed | Full Overlay Metal Sheet Door, Chrome Plated Handle | 2" - 20 m | - | Optional | 600 | 700 | 200 | 560 | 660 |
| SE2-2212.3 | Recessed | Full Overlay Metal Sheet Door, Chrome Plated Handle | 2" - 30 m | - | Optional | 600 | 700 | 200 | 560 | 660 |
| SE2-2222.1 | Surface | Full Overlay Metal Sheet Door, Chrome Plated Handle | 2" - 20 m | - | Optional | 600 | 700 | 200 | 600 | 700 |
| SE2-2222.3 | Surface | Full Overlay Metal Sheet Door, Chrome Plated Handle | 2" - 30 m | - | Optional | 600 | 700 | 200 | 600 | 700 |

CABINET HOUSING

- Produced from 1.2 mm mild steel (DKP).
- Flaps at every corner for fire valve installation
- Hose reel can be left or right mounted
- Surface mount or recessed mount types obtainable

HOSE REEL

- Reel crank allows hose reel to be opened at an angle of 270°.
- 2" Fire valve and 2" hose sleeve
- 2" Fire lance and 2" hose sleeve
- 2" lat flay fire hose
- All connections are made with whipcheck safety cables instead of clamps.

CABINET DOOR

- Full overlay metal sheet door, chrome plated handle
- Laser cut warning signs on the surface
- After the housing has been mounted on the wall, the doors can be simply attached to the housing with 4 screws.
- 180 degree opening door with semi-hidden continuous hinges.