

## FIRE CABINET


## LAY- FLAT HOSE

INSET METAL SHEET DOOR



► SE2-2213.1

- 2½" flat type fire hose, 2½" fire valve and 2½" fire lance are optional
- All parts are painted with electrostatic powder paint at 200°C, optionally in the colours RAL 9010 white, RAL 3003 red or RAL1013 champagne. Other colours are available to meet specific needs.
- This fire cabinet models are in compliance with EN 671-1.
- Fire cabinets and their doors can be optionally produced from stainless steel and with decorative cutouts to suit various architectural requirements.
- All models can be manufactured with front and rear doors.



CODE	MOUNTING STYLE	MODULAR DOOR TYPE	HOSE DIAMETER & LENGTH	TUBE CAPACITY	LIGHTING	W mm	H mm	D mm	W <sub>i</sub> mm	H <sub>i</sub> mm
SE2-2213.1	Recessed	Inset Metal Sheet Door	2" - 20 m	-	Optional	600	700	200	560	660
SE2-2213.3	Recessed	Inset Metal Sheet Door	2" - 30 m	-	Optional	600	700	200	560	660
SE2-2223.1	Surface	Inset Metal Sheet Door	2" - 20 m	-	Optional	600	700	200	600	700
SE2-2223.3	Surface	Inset Metal Sheet Door	2" - 30 m	-	Optional	600	700	200	600	700

### ► CABINET HOUSING

- Produced from 1.2 mm mild steel (DKP).
- Flaps at every corner for fire valve installation
- Hose reel can be left or right mounted
- Surface mount or recessed mount types obtainable

### ► HOSE REEL

- Reel crank allows hose reel to be opened at an angle of 270°.
- 2" Fire valve and 2" hose sleeve
- 2" Fire lance and 2" hose sleeve
- 2" lat flay fire hose
- All connections are made with whipcheck safety cables instead of clamps.

### ► CABINET DOOR

- Inset metal sheet door with radial frame, chrome plated handle
- Relief warning signs on the surface.
- After the housing has been mounted on the wall, the doors can be simply attached to the housing with 4 screws.
- 180 degree opening door with continuous hinges, optionally stainless hinges or invisible hinges obtainable.