**FIRE CABINET** 




## LAY - FLAT HOSE


FULL OVERLAY METAL SHEET DOOR, CHROME PLATED HANDLE, HORIZONTAL FIRE EXTINGUISHER SECTION FOR 2 TUBES



 $2\frac{1}{2}$ " flat type fire hose,  $2\frac{1}{2}$ " fire valve and  $2\frac{1}{2}$ " fire lance are optional

- All parts are painted with electrostatic powder paint at 200°C, optionally in the colours RAL 9010 white, RAL 3003 red or RAL1013 champagne. Other colours are available to meet specific needs.
- This fire cabinet models are in compliance with EN 671-1.
- Fire cabinets and their doors can be optionally produced from stainless steel and with decorative cutouts to suit various architectural requirements.
- All models can be manufactured with front and rear doors.





CODE	MOUNTING STYLE	MODULAR DOOR TYPE	HOSE DIAMETER & LENGTH	TUBE CAPACITY	LIGHTING	W mm	H mm	D mm	W, mm	H, mm
SE2-2612.1	Recessed	Full Overlay Metal Sheet Door, Chrome Plated Handle	2" - 20 m	2 Tube / 6 kg	Optional	700	1100	200	660	1060
SE2-2612.3	Recessed	Full Overlay Metal Sheet Door, Chrome Plated Handle	2" - 30 m	2 Tube / 6 kg	Optional	700	1100	200	660	1060
SE2-2622.1	Surface	Full Overlay Metal Sheet Door, Chrome Plated Handle	2" - 20 m	2 Tube / 6 kg	Optional	700	1100	200	700	1100
SE2-2622.3	Surface	Full Overlay Metal Sheet Door, Chrome Plated Handle	2" - 30 m	2 Tube / 6 kg	Optional	700	1100	200	700	1100

## ► CABINET HOUSING

- Produced from 1.2 mm mild steel (DKP). ٠
- Flaps at every corner for fire valve installation .
- Hose reel can be left or right mounted •
- Surface mount or recessed mount types . obtainable.

## **HOSE REEL**

- Reel crank allows hose reel to be opened at an angle
- of 270°.
- 2" Fire valve and 2" hose sleeve
  2" Fire lance and 2" hose sleeve
- 2" lat flay fire hose
- . All connections are made with whipcheck safety cables instead of clamps

## **CABINET DOOR**

- Inset metal sheet door chrome plated handle
- Laser cut warning signs on the surface. •
- After the housing has been mounted on the wall, the doors can be simply attached to the housing with 4 screws.
- 180 degree opening door with semi-hidden continuous hinges.

We reserve the right to make changes in design and size. | Our products are patented by the Turkish Patent Office