

**FIRE CABINET**


**LAY – FLAT HOSE**

SINGLE FULL OVERLAY METAL SHEET DOOR, CHROME PLATED HANDLE, DOUBLE HOSE REEL, VERTICAL SECTION FOR 2 TUBES



► SE2-3112.1

- 2½" flat type fire hose, 2½" fire valve and 2½" fire lance are optional
- All parts are painted with electrostatic powder paint at 200°C, optionally in the colours RAL 9010 white, RAL 3003 red or RAL1013 champagne. Other colours are available to meet specific needs.
- This fire cabinet models are in compliance with EN 671-1.
- Fire cabinets and their doors can be optionally produced from stainless steel and with decorative cutouts to suit various architectural requirements.
- All models can be manufactured with front and rear doors.



| CODE       | MOUNTING STYLE | MODULAR DOOR TYPE                                   | HOSE DIAMETER & LENGTH | TUBE CAPACITY | LIGHTING | W mm | H mm | D mm | W <sub>1</sub> mm | H <sub>1</sub> mm |
|------------|----------------|---|------------------------|---------------|----------|------|------|------|-------------------|-------------------|
| SE2-3112.1 | Recessed       | Full Overlay Metal Sheet Door, Chrome Plated Handle | 2" - 20 m              | 2 Tube / 6 kg | Optional | 800  | 1400 | 200  | 760               | 1360              |
| SE2-3112.3 | Recessed       | Full Overlay Metal Sheet Door, Chrome Plated Handle | 2" - 30 m              | 2 Tube / 6 kg | Optional | 800  | 1400 | 200  | 760               | 1360              |
| SE2-3122.1 | Surface        | Full Overlay Metal Sheet Door, Chrome Plated Handle | 2" - 20 m              | 2 Tube / 6 kg | Optional | 800  | 1400 | 200  | 800               | 1400              |
| SE2-3122.3 | Surface        | Full Overlay Metal Sheet Door, Chrome Plated Handle | 2" - 30 m              | 2 Tube / 6 kg | Optional | 800  | 1400 | 200  | 800               | 1400              |

► **CABINET HOUSING**

- Produced from 1.2 mm mild steel (DKP).
- Flaps at every corner for fire valve installation.
- Hose reel can be left or right mounted.
- Surface mount or recessed mount types obtainable.

► **HOSE REEL**

- Reel crank allows hose reel to be opened at an angle of 270°.
- 2" Fire valve and 2" hose sleeve
- 2" Fire lance and 2" hose sleeve
- 2" flat fire hose
- All connections are made with whipcheck safety cables instead of clamps.

► **CABINET DOOR**

- Full overlay metal sheet door, chrome plated handle
- Laser cut warning signs on the surface
- After the housing has been mounted on the wall, the doors can be simply attached to the housing with 4 screws.
- 180 degree opening door with semi-hidden continuous hinges.