

FIRE EXTINGUISHING TUBES
DRY CHEMICAL POWDER FIRE EXTINGUISHING TUBES



CAPACITY	TYPE	EXTINGUISHER CLASS	OPERATING PRESSURE	TEST PRESSURE	SPRAY DISTANCE
1 kg	Portable Type	A,B,C	17 Bar	25 Bar	3 - 4 m.
2 kg	Portable Type	A,B,C	17 Bar	25 Bar	3 - 4 m.
4 kg	Portable Type	A,B,C	17 Bar	25 Bar	3 - 4 m.
6 kg	Portable Type	A,B,C	17 Bar	25 Bar	4 - 5 m.
9 kg	Portable Type	A,B,C	17 Bar	25 Bar	4 - 5 m.
12 kg	Portable Type	A,B,C	17 Bar	25 Bar	4 - 5 m.
12 kg	Mobile Type	A,B,C	18 Bar	25 Bar	4 - 5 m.
25 kg	Mobile Type	A,B,C	18 Bar	25 Bar	4 - 5 m.
50 kg	Mobile Type	A,B,C	18 Bar	30 Bar	4 - 5 m.
250 kg	Cart Type	A,B,C	22 Bar	33 Bar	10 - 12 m.

- Preferred in fires caused by flammable materials, flammable liquids.
- CE 0036 Certified.
- TS 862 EN 3 Certified.
- ISO 9001 Certified.
- 2 year warranty.
- With manometer
- Spinned body produced of 1,5 mm metal sheet.
- N2 (Nitrogen) propellant.
- -20°C / +60°C operating temperature.
- Safety valve.
- With hanger.
- Carts and wheels suitable for model and capacity
- Extinguishing medium is dry chemical powder.