

FIRE CABINET


1" SEMI - RIGID HOSE REEL, AXIAL WATER SUPPLY

INSET GLASS DOOR, HORIZONTAL FIRE EXTINGUISHER SECTION



SE1-2014.1

- All parts are painted with electrostatic powder paint at 200°C, optionally in the colours RAL 9010 white, RAL 3003 red or RAL 1013 champagne. Other colours are available to meet specific needs.
- This fire cabinet models are in compliance with EN 671-1.
- Fire cabinets and their doors can be optionally produced from stainless steel and with decorative cutouts to suit various architectural requirements.
- All models can be manufactured with front and rear doors.



CODE	MOUNTING STYLE	MODULAR DOOR TYPE	HOSE DIAMETER & LENGTH	TUBE CAPACITY	LIGHTING	W mm	H mm	D mm	W ₁ mm	H ₁ mm
SE1-2014.1	Recessed	Inset Glass Door	1" - 20 m	1 Tube / 6 kg	Optional	800	970	200	760	930
SE1-2014.2	Recessed	Inset Glass Door	1" - 25 m	1 Tube / 6 kg	Optional	800	970	200	760	930
SE1-2014.3	Recessed	Inset Glass Door	1" - 30 m	1 Tube / 6 kg	Optional	800	970	200	760	930
SE1-2024.1	Surface	Inset Glass Door	1" - 20 m	1 Tube / 6 kg	Optional	800	970	200	800	970
SE1-2024.2	Surface	Inset Glass Door	1" - 25 m	1 Tube / 6 kg	Optional	800	970	200	800	970
SE1-2024.3	Surface	Inset Glass Door	1" - 30 m	1 Tube / 6 kg	Optional	800	970	200	800	970

CABINET HOUSING

- Produced from 1.2 mm mild steel (DKP).
- Flaps at every corner for fire valve installation.
- Hose reel can be left or right mounted.
- Surface mount or recessed mount types obtainable.

HOSE REEL

- Axial water supply. Water inlet made of rust-resistant material.
- Solid 6 mm crank allows hose reel to be opened at an angle of 270°.
- Includes 2" fire valve and 2" x1" reducing valve.
- Nozzle with 1" jet / spray / lock setting.
- 1" round, semi - rigid hose.
- Inside hardened connection hose connects hose reel with valve
- All connections are made with press fitting instead of clamp fitting
- All hose reels have been tested.

CABINET DOOR

- Inset glass door with frame, chrome plated handle
- 4 mm thick tempered smoke glass
- Screen printed warning signs are fired at 700°C
- After the housing has been mounted on the wall, the doors can be simply attached to the housing with 4 screws.
- 180 degree opening door with continuous hinges, optionally stainless hinges or invisible hinges obtainable